



# PRODUCT DATA

---

## **FLEX-GUARD PE**

Expandable Monofilament Sleeving

### **DESCRIPTION**

**FLEX-GUARD PE** is a braided sleeving produced by braiding PET (Polyethylene terephthalate) monofilament into a tubular sleeve. **FLEX-GUARD PE** is a tough yet lightweight sleeving typically used to jacket cable assemblies, wire harnesses, and industrial hoses where additional protection is desired without sacrificing flexibility and overall weight. This sleeving is UL recognized and CSA approved for use up to 125°C. It is available in a heavy duty (PE/HD) and a tight weave (PE/TW) construction for more critical applications.

### **FEATURES**

**FLEX-GUARD PE** demonstrates excellent chemical and fungus resistance while providing good mechanical properties. It has an open weave construction, thus allowing each size to enlarge up to three times its original diameter. This expansion quality makes it easy to apply and slip on quickly over irregular shapes. Its good flexibility, which is retained at low temperatures, allows for easy flexing in any direction and it can neatly capture a number of different size items within one length.

### **APPLICATIONS**

**FLEX-GUARD PE** is commonly used over wires, wire bundles and harnesses, cable assemblies, flat ribbon cable, tubing and hoses where it provides a tough, durable protection. Its resistance to abrasion and cut through makes it ideal for many industrial and electrical applications. The open weave construction allows for complete drainage, prevents condensation and provides for dissipation of heat and moisture. Its excellent chemical resistance permits its use in harsh fluid environments including oils, salt water, fuels, most common cleaners and solvents and many chemicals. Its flexing capability makes the product ideal for application in machine tools, automatic equipment and robotics where wires and tubes are often required to flex freely during operating cycles. The low temperature properties of **FLEX-GUARD PE** make it suitable for exposure to all weather conditions.

### **STANDARD COLORS**

Black and Clear

### **OTHER COLORS**

Red, Orange, Yellow, Green, Blue and Gray

## FLEX-GUARD PE

### PROPERTIES

PROPERTY	TEST METHOD	PERFORMANCE
Tensile Strength	ASTM D-876	100,000 psi
Elongation	ASTM D-876	20%
Specific Gravity	ASTM D-876	1.31
Moisture Absorption (24 hours)	ASTM D-570	0.08%
Shrinkage @ 180°C		4%
Max. Operating Temperature	UL 224	125°C
Melt Temperature	ASTM D-2117	250°C
Low Temperature Flexibility	MIL I 23053 -E	-70°C
Flexural Modulus 10 <sup>3</sup> psi @ 73°F	ASTM D-790	400
Fungus Resistance	MIL STD 810 (508)	No Growth
Copper Corrosivity	MIL I 23053	No Effect

### FLUID RESISTANCE

Testing verifies that there is virtually no effect on the tensile strength and only a slight reduction in elongation (approx. 5%) of FLEX-GUARD PE when exposed to the following fluids: Cleaning Fluid, De-icing Fluid, Fuel Oil, Gasoline, Hydraulic Fluid, Lubricating Oil, Salt Water, and Solvents.

### DIMENSIONS

Size Nominal I.D.	Size Range (inches)	Approx. Weight lbs./1000 feet	Std. Spool put-up
1/8"	3/32" - 1/4"	1.9	1000 ft.
1/4"	1/8" - 3/8"	2.7	1000 ft.
3/8"	1/4" - 5/8"	6.0	500 ft.
1/2"	1/4" - 3/4"	7.5	500 ft.
3/4"	1/2" - 1-1/4"	12.5	250 ft.
1-1/4"	7/8" - 1-3/4"	15.9	250 ft.
1-1/2"	1" - 2"	19.6	250 ft.
1-3/4"	1-1/4" - 2-3/4"	26.3	200 ft.
2"	1-1/2" - 3-1/2"	34.0	200 ft.
2-1/2"	1-3/4" - 4-1/2"	46.5	100 ft.
3"	1-7/8" - 4-1/2"	47.0	100 ft.

The information provided above represents average values and is believed to be reliable. Alta Technologies, Inc. make no warranties as to its accuracy and disclaims any liability in connection with its use. It is provided for general use only and should not be incorporated into any specific specifications.