

Dimensions and Weights

Standard Materials	Size Inches	Part No.	Outside Diameter O.D. Inches	Wall Thickness Inches	Nominal Inside Diameter I.D. Inches	Pitch Inches	Weight Lbs/ M Ft.	Maximum Bundle Range Inches	
Natural Polyethylene	1/8	HT 1/8C	.125	.032	.061	.187	4	1/16 to 1/2	
	3/16	HT 3/16C	.187	.030	.127	.250	6	1/8 to 1-1/2	
	1/4	HT 1/4C2 Thin Wall	.250	.035	.180	.375	9	3/16 to 2	
	1/4	HT 1/4C	.250	.045	.160	.375	12	3/16 to 2	
	3/8	HT 3/8C	.375	.052	.271	.438	22	5/16 to 3	
	1/2	HT 1/2C2 Thin Wall	.500	.040	.420	.563	24	3/8 to 4	
	1/2	HT 1/2C	.500	.062	.376	.563	35	3/8 to 4	
	5/8	HT 5/8C	.625	.062	.500	.625	44	1/2 to 4-1/2	
	3/4	HT 3/4C	.750	.065	.620	.750	57	3/4 to 5	
	1	HT 1C	1.00	.080	.840	1.00	94	1 to 7	
	1-1/4	HT 1-1/4C	1.25	.090	1.070	1.25	133	1-1/4 to 8	
	1-1/2	HT 1-1/2C	1.50	.100	1.30	1.50	178	1-1/2 to 10	
	Polyethylene in Colors	1/8	HT 1/8C-COLOR	.125	.032	.061	.187	4	1/16 to 1/2
		1/4	HT 1/4C-COLOR	.250	.045	.160	.375	12	3/16 to 2
3/8		HT 3/8C-COLOR	.375	.052	.271	.438	22	5/16 to 3	
1/2		HT 1/2C-COLOR	.500	.062	.375	.563	35	3/8 to 4	
3/4		HT 3/4C-COLOR	.750	.065	.620	.750	57	3/4 to 5	
1		HT 1C-COLOR	1.00	.080	.840	1.00	94	1 to 7	
Black Polyethylene	1/8	HT 1/8UR	.125	.032	.061	.187	4	1/16 to 1/2	
	3/16	HT 3/16UR	.187	.030	.127	.250	6	1/8 to 1-1/3	
	1/4	HT 1/4UR2-Thin Wall	.250	.035	.180	.375	9	3/16 to 2	
	1/4	HT 1/4UR	.250	.045	.160	.375	12	3/16 to 2	
	3/8	HT 3/8UR	.375	.052	.271	.438	22	5/16 to 3	
	1/2	HT 1/2UR2-Thin Wall	.500	.040	.420	.500	24	3/8 to 4	
	1/2	HT 1/2UR	.500	.062	.376	.500	35	3/8 to 4	
	5/8	HT 5/8UR	.625	.062	.500	.625	44	1/2 to 4-1/2	
	3/4	HT 3/4UR	.750	.065	.620	.750	57	3/4 to 5	
	1	HT 1UR	1.00	.080	.840	1.00	94	1 to 7	
	1-1/4	HT 1-1/4UR	1.25	.090	1.070	1.25	133	1-1/4 to 8	
	1-1/2	HT 1-1/2UR	1.50	.100	1.30	1.50	178	1-1/2 to 10	
	Fire Resistant White	1/8	HT 1/8R	.125	.032	.061	.187	6	1/16 to 1/2
		3/16	HT 3/16R	.187	.040	.107	.250	8	1/8 to 1-1/2
1/4		HT 1/4R	.250	.045	.160	.375	17	3/16 to 2	
3/8		HT 3/8R	.375	.052	.271	.438	29	5/16 to 3	
1/2		HT 1/2R	.500	.062	.376	.563	52	3/8 to 4	
5/8		HT 5/8R	.625	.062	.500	.625	67	1/2 to 4-1/2	
3/4		HT 3/4R	.750	.065	.620	.750	85	3/4 to 5	
1		HT 1R	1.00	.080	.840	1.00	156	1 to 7	
Fire Resistant Black		1/8	HT 1/8R-B	.125	.032	.061	.187	6	1/16 to 1/2
	1/4	HT 1/4R-B	.250	.045	.160	.375	17	3/16 to 2	
	3/8	HT 3/8R-B	.375	.052	.271	.438	29	5/16 to 3	
	1/2	HT 1/2R-B	.500	.062	.376	.563	52	3/8 to 4	
	3/4	HT 3/4R-B	.750	.065	.620	.750	85	3/4 to 4-1/2	
	1	HT 1R-B	1.00	.080	.840	1.00	156	1 to 7	
Nylon	1/8	HT 1/8N	.125	.015	.095	.187	3	1/16 to 1/2	
	3/16	HT 3/16N	.187	.020	.147	.250	6	1/8 to 1-1/2	
	1/4	HT 1/4N	.250	.025	.200	.375	9	3/16 to 2	
	3/8	HT 3/8N	.375	.035	.305	.438	18	5/16 to 3	
	1/2	HT 1/2N	.500	.035	.430	.500	25	3/8 to 4	
	5/8	HT 5/8N	.625	.032	.561	.625	30	1/2 to 4-1/2	
	3/4	HT 3/4N	.750	.032	.686	.750	36	1/2 to 5	
	1	HT 1N	1.00	.032	.936	1.00	50	1 to 7	
Black Nylon	1/8	HT 1/8N-B	.125	.015	.095	.187	3	1/16 to 1/2	
	3/16	HT 3/16N-B	.187	.020	.147	.250	6	1/8 to 1-1/2	
	1/4	HT 1/4N-B	.250	.025	.200	.375	9	3/16 to 2	
	3/8	HT 3/8N-B	.375	.035	.305	.438	18	5/16 to 3	
	1/2	HT 1/2N-B	.500	.035	.430	.500	25	3/8 to 4	
	5/8	HT 5/8N-B	.625	.032	.561	.625	30	1/2 to 4-1/2	
	3/4	HT 3/4N-B	.750	.032	.686	.750	36	1/2 to 5	
	7/8	HT 7/8N-B	.875	.032	.811	.875	48	5/8 to 6	
	1	HT 1N-B	1.00	.032	.936	1.00	50	1 to 7	
PTFE Available in Black and a wide selection of colors	1/16	HT 1/16T	.062	.016	.030	.062	4.2	1/32 to 1/8	
	1/8	HT 1/8T1	.125	.030	.065	.187	9.4	1/16 to 1/2	
	1/8	HT 1/8T2-Thin Wall	.125	.020	.085	.187	7.4	1/16 to 1/2	
	3/16	HT 3/16T	.187	.030	.127	.250	15.2	1/8 to 1-1/2	
	1/4	HT 1/4T	.250	.030	.187	.375	20.7	3/16 to 2	
	3/8	HT 3/8T	.375	.030	.312	.438	36.5	5/16 to 2-1/2	
	1/2	HT 1/2T	.500	.030	.438	.500	50.5	3/8 to 3	
	3/4	HT 3/4T	.750	.032	.686	.750	81.3	1/2 to 4	
	1	HT 1T	1.00	.040	.920	1.00	175.0	3/4 to 5	