



# Shrink-Kon<sup>®</sup>

## Heavy-Wall Heat-Shrinkable Tubing

T&B Catalog Number:

**UPC Number:** HS40-400-4  
**Status:** 78621087862  
**Description:** Active

Heavy-Wall Heat-Shrinkable Tubing for Cable Range 2/0 - 350 MCM, Expanded Dia. 1.5, Length 48 in., rated for 600V, 90 degrees continuous use, Material: Cross-linked polyolefin with thermoplastic adhesive liner, Black

### Features

Made of thermally stabilized cross-linked polyolefin, enabling a recovered wall thickness greater than that of the cable jacket replaced.

Withstands severe mechanical requirements of U.R.D., submersible, and direct burial installations. Tubing, featuring and internally applied sealant, offers protection against moisture, and may be used over lead, steel, aluminum, copper, standard plastic and elastomeric insulating materials.

### General

Style	HS Series - Black
Color	Black
Temperature Range	-55°C - 110°C
Shrink Ratio	3:1

### Dimension Information

Minimum Expanded I.D. (inches)	1.5
Maximum Recovered I.D. (inches)	0.47
Nominal Recovered Wall (inches)	0.16
Cable Range	2/0 - 350 MCM
Standard Length (inches)	48

### Specifications

Shrink Temperature	120°C
Voltage Rating	600V

### Packaging

T&B Order Multiple	5
Package in Units	5
T&B Sold in UOM	Each
T&B Weight Per UOM	80 lbs. per 100

### Application Support

MSDS Number	msds-0012-tb2msds-0127-tb2
T&B Sales Drawings	wsd-000473
Specifications	Available on Website
Overview	Available on Website

### Notes

All lengths have factory-applied sealant.

### Certifications

RoHS Compliance	Yes
-----------------	-----

## Certifications



File Nbr:  
E9809

### For further technical assistance, please contact us...

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)