



ZEUS INDUSTRIAL PRODUCTS, INC.
 P.O. Box 2167, 501 Boulevard Street,
 Orangeburg, SC 29115
 1-800-526-3842 • 1-803-531-2174
 FAX: 803-533-5694

TFE HEAT SHRINK TUBING 2 TO 1 SHRINK RATIO BULLETINS 9 • 10 • 10-M

ZEUS is a pioneer, leading producer, and the most reliable source for Heat Shrink Tubing. Technical details and helpful comments on working with Heat Shrink Tubing appear elsewhere in this Catalog. For the mechanical, electrical and thermal characteristics of TFE see the "SUMMARY OF PROPERTIES" table.

STANDARD WALL Bulletin 9					THIN WALL Bulletin 10					LIGHTWEIGHT WALL Bulletin 10M				
Ordered as AWG Size No.	Expanded I.D. Min. (Inches)	Recovered I.D. Max. (Inches)	Recovered Wall Thickness (Inches)		Ordered as AWG Size No.	Expanded I.D. Min. (Inches)	Recovered I.D. Max. (Inches)	Recovered Wall Thickness (Inches)		Ordered as AWG Size No.	Expanded I.D. Min. (Inches)	Recovered I.D. Max. (Inches)	Recovered Wall Thickness (Inches)	
			Nom.	Tol.				Nom.	Tol.				Nom.	Tol.
30	.034	.015	.009	±.002	30	.034	.015	.009	±.002	30	.034	.015	.006	±.002
28	.038	.018	.009	±.002	28	.038	.018	.009	±.002	28	.038	.018	.006	±.002
26	.046	.022	.010	±.002	26	.046	.022	.010	±.002	26	.046	.022	.006	±.002
24	.050	.027	.012	±.002	24	.050	.027	.010	±.002	24	.050	.025	.006	±.002
22	.055	.032	.012	±.002	22	.055	.032	.012	±.003	22	.055	.031	.006	±.002
20	.060	.039	.016	±.003	20	.060	.039	.012	±.003	20	.060	.038	.006	±.002
19	.065	.043	.016	±.003	19	.065	.043	.012	±.003	19	.065	.043	.006	±.002
18	.076	.049	.016	±.003	18	.076	.049	.012	±.003	18	.076	.046	.006	±.002
17	.085	.054	.016	±.003	17	.085	.054	.012	±.003	17	.085	.054	.006	±.002
16	.090	.061	.016	±.003	16	.093	.061	.012	±.003	16	.093	.057	.006	±.002
15	.110	.067	.016	±.003	15	.110	.067	.012	±.003	15	.110	.063	.006	±.002
14	.120	.072	.016	±.003	14	.120	.072	.012	±.003	14	.120	.072	.008	±.002
13	.140	.080	.016	±.003	13	.140	.080	.012	±.003	13	.140	.080	.008	±.002
12	.150	.089	.016	±.003	12	.150	.089	.012	±.003	12	.150	.089	.008	±.002
11	.170	.101	.016	±.003	11	.170	.101	.012	±.003	11	.170	.099	.008	±.002
10	.191	.112	.016	±.003	10	.191	.112	.012	±.003	10	.191	.110	.008	±.002
9	.205	.124	.020	±.004	9	.205	.124	.015	±.004	9	.205	.122	.008	±.002
8	.240	.141	.020	±.004	8	.240	.141	.015	±.004	8	.240	.139	.008	±.002
7	.270	.158	.020	±.004	7	.270	.158	.015	±.004	7	.270	.154	.008	±.002
6	.302	.178	.020	±.004	6	.302	.178	.015	±.004	6	.302	.172	.010	±.003
5	.320	.198	.020	±.004	5	.320	.198	.015	±.004	5	.320	.192	.010	±.003
4	.370	.224	.020	±.004	4	.370	.224	.015	±.004	4	.370	.214	.010	±.003
3	.390	.249	.020	±.004	3	.390	.249	.015	±.004	3	.390	.241	.010	±.003
2	.430	.278	.020	±.004	2	.430	.278	.015	±.004	2	.430	.270	.010	±.003
1	.450	.311	.020	±.004	1	.450	.311	.015	±.004	1	.450	.301	.010	±.003
0	.470	.347	.020	±.004	0	.470	.347	.015	±.004	0	.470	.347	.012	±.003
										Fractional Inch				
										1/8	.215	.130	.008	±.002
										1/4	.410	.260	.010	±.003
										5/16	.470	.329	.012	±.003

APPLICABLE SPECIFICATIONS:
 Bulletin 9, Standard Wall MIL-I-23053/12
 Bulletin 10, Thin Wall, MIL-I-23053/12
 Bulletin 10M, Lightweight, MIL-I-23053/12

On all cases of military or commercial specifications, latest revisions apply. Supplied in natural unless otherwise specified. Mil. Std. 104 colors on request.

CUSTOM SPECIFICATIONS AND TOLERANCES UPON REQUEST

Four-foot sticks of Heat Shrink tubing are standard packaging lengths. Shorter pieces, longer pieces, or cut pieces to size are available upon request. Extremely long continuous lengths are sometimes available depending on specifications. Inquire for feasibility and pricing.